




Bimetal Thermoeter 雙金屬溫度計

Model 型號	BTA (Adjustable Type) 可調角式	BTI (Bottom Type) 直立式	BTT (Back Type) 背接式
			
Case diameter 錶面徑	2", 3", 4", 5", 6"		
Case material 外殼材質	SUS 304 / SUS 316		
Case construction 外殼構造	Packing sealed and bezel assembly (墊片密合及嵌入組裝)		
Transparent plate 視窗	Resin or safety glass (樹脂或安全玻璃鏡面)		
Dial scale plate 面板	White background with black pointer and black figures (白色面板, 黑色指針, 黑色數字)		
Temperature range 溫度範圍	-50~-600 = °C / °F (0~+50, -50~+50, -20~+80, -20~+120, 0~+100, 0~+120, 0~+150, 0~+160, 0~+200, 0~+250, 0~+300, 0~+350, 0~+400, 0~+500, 0~+600 °C/°F or dual, other ranges are available) (刻度可設定°C或°F, 或雙刻度。溫度範圍可自選)		
Pointer reset 零點調整	External adjustable (外部調整)	Inner adjustable (內部調整)	Inner adjustable (內部調整)
Accuracy 精確度	+ / -1%		
Stem diameter 感測棒直徑	Ø 6.35 mm ~ 9.5 mm		
Stem length 感測棒長度	2"~50"		
Stem material 感測棒材質	SUS 304 / SUS 316		
External process thread 接續牙口	1/4", 3/8", 1/2", 3/4" PT or NPT. other connections are available.		
Temperature over-range 溫度過載保護	10% over-range on higher temperature range will not harm its accuracy. (溫度超過10%將不影響其精確度)		
Contact Type 接點型式	1 SPST or 2 SPST (Relay Load: 110VAC / 0.4 A) Set Value 1 (Sv1): NO or NC is available. Set Value 2 (Sv2): NO or NC is available. If order, please note Sv1, Sv2 is NO or NC		None



Order by specify:

Model= 1 / 2 / 3 / 4 / 5 / 6 / 7 /

- | | |
|---|--|
| <p>1. Model - Dial Size - Case Material 型號及面徑尺寸、材質</p> <p>3. Stem Material - Diameter 感測棒材質、直徑</p> <p>5. Mounting Size 接續方式</p> <p>7. Thermowell 保護套管</p> | <p>2. Temperature Range 溫度範圍</p> <p>4. Stem Length 感測棒長度</p> <p>6. Contact Type 電氣接點</p> |
|---|--|

if item (6), (7) is not required, please note "#", 若不須(6)電氣接點, (7)保護套管, 請註明 "#"

Remote reading type Thermoeter 雙金屬溫度計

	RBTW (WALL/EAR MOUNTING) 壁掛式	RBTWF WALLMOUNTING WITH FLANGE TYPE 埋入式法蘭面
Model 型號		
Case diameter 錶面徑	4" , 6"	
Case material 外殼材質	SUS 304 / SUS 316	
Case construction 外殼構造	Packing sealed and bezel assembly (墊片密合及嵌入組裝)	
Transparent plate 視窗	Resin or safety glass (樹脂或安全玻璃鏡面)	
Dial scale plate 面板	White background with black pointer and black figures (白色面板，黑色指針，黑色數字)	
Temperature range 溫度範圍	-50~-600= °C / °F (0~+50, -50~+50, -20~+80, -20~+120, 0~+100, 0~+120, 0~+150, 0~+160, 0~+200, 0~+250, 0~+300, 0~+350, 0~+400, 0~+500, 0~+600 °C/°F or dual, other ranges are available) (刻度可設定°C或°F，或雙刻度。溫度範圍可自選)	
Pointer reset 零點調整	External adjustable (外部調整)	
Accuracy 精確度	+ / -1%	
Stem diameter 感測棒直徑	Ø 6.35 mm ~ 12 mm	
Stem length 感測棒長度	Standard Length 150 mm, or by order	
Stem material 感測棒材質	SUS 304 / SUS 316	
Capillary length 毛細管長度	3 M ~ 20 M	
External process thread 接續牙口	1/4", 3/8", 1/2", 3/4" PT or NPT. other connections are available.	
Temperature over-range 溫度過載保護	10% over-range on higher temperature range will not harm its accuracy. (溫度超過10%將不影響其精確度)	
Contact Type 接點型式	1 SPST or 2 SPST (Relay Load: 110VAC / 0.4 A) Set Value 1 (Sv1): NO or NC is available. Set Value 2 (Sv2): NO or NC is available. If order, please note Sv1, Sv2 is NO or NC	

Order by specify:

Model= 1 / 2 / 3 / 4 / 5 / 6 / 7 / 8

- | | |
|--|--|
| 1. Model - Dial Size - Case Material 型號及面徑尺寸、材質
3. Stem Material - Diameter 感測棒材質、直徑
5. Capillary Length 毛細管長度
7. Contact Type 電氣接點 | 2. Temperature Range 溫度範圍
4. Stem Lenger 感測棒長度
6. Mounting Size 接續方式
8. Thermowell 保護套管 |
|--|--|

if item (7), (8) is not required, please note "#", 若不須(7)電氣接點，(8)保護套管，請註明 "#"